APPROX. WEIGHT (LBS)
160

ECO No	DESCRIPTION	REV BY	DATE



TOP VIEW



BOTTOM VIEW



DETAIL C
(3 PLACES)





DETAIL D



CUSTOMER CONNECTION
DETAIL VIEW



DETAIL A
CUSTOMER CONNECTION
DETAIL VIEW



DETAIL B
(3 PLACES)



FRONT VIEW



SIDE VIEW

NOTES:

1. TERMINAL WIRE RANGE: 4-14 AWG.
2. TERMINAL SCREW TIGHTENING TORQUE: 16 IN\LBS.
3. REFER TO USER MANUAL FOR FURTHER INSTRUCTIONS.
4. FILTER INCLUDES: CAP-338TP(QTY. 2), CAP-345TP(QTY. 1 AND CAP-346TP(QTY. 1) .
5. CUSTOMER MUST PROVIDE PROPER COOLING AIRFLOW. MUST BE A MINIMUM OF 400 LINEAR FT/MIN.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM]
TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
POWER QUALITY. SOLVED.
A STEEL PARTNERS COMPANY

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455.4683
262.253.8200

MATERIAL

DRAWN	DATE
MN	07/06/20
CHECKED	DATE
MN	07/06/20
APPROVED	DATE
JG	07/08/20

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

MATRIX-E, 240A, 480V,
60Hz, OPEN PANEL

SIZE	DWG No.	REV
D	CD MAEP0240D	00

SCALE 1:2 SHEET 1 OF 1