



APPROX. WEIGHT (LBS)
149



ECO No	DESCRIPTION	REV BY	DATE
M10374	REPLACED CAPPANEL-017 TO CAPPANEL-017C	AB	09/26/18




FRONT VIEW
(PANELS REMOVED)




SIDE VIEW
(PANELS REMOVED)




DETAIL A
CUSTOMER CONNECTION
DETAIL VIEW




BOTTOM VIEW



TOP VIEW
(PANELS REMOVED)



- NOTES:**
1. TERMINAL SCREW TIGHTENING TORQUE: 16 IN/LBS.
 2. WIRE RANGE: 4-14 AWG.
 3. REFER TO USER MANUAL FOR COMPLETE INSTALLATION INSTRUCTIONS.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION			
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE: ANGLES: ± 1 ° 1 PLACE .X: ± .1 [2.5] 2 PLACE .XX: ± .03 [0.76] 3 PLACE .XXX: ± .010 [0.254]		 N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455.4683 262.253.8200		MATRIX SINGLE PH FILTER 38A, 240V, 60HZ NEMA 3R ENCL			
		DRAWN	DATE	SIZE	DWG No.	REV	
		MN	02/11/15				
		CHECKED	DATE	SCALE	1:4	SHEET 1 OF 1	
		AB	09/26/18				
		APPROVED	DATE				
		JG	10/01/18				