





| WEIGHT (LBS) | INDUCTANCE | LOSS (WATTS) |
|--------------|------------|--------------|
| 2 | 15mH | 4.2 |

| ECO No | DESCRIPTION | REV BY | DATE |
|--------|----------------------|--------|----------|
| M8128 | REDRAW IN SOLIDWORKS | JP | 08/07/12 |



VIEW A-A



- NOTES:
1. TERMINAL SCREW TIGHTENING TORQUE; 4.5 in-lb MAX.
2. WIRE RANGE: 22-10 AWG.

| THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS | | MATERIAL | | CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION | | |
|--|--|---|------------------|--|--------------------------|-----------|
| CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION | | | | DESCRIPTION | | |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE: ANGLES: ± 1 ° 1 PLACE .X: ± .1 [2.5] 2 PLACE .XX: ± .03 [0.76] 3 PLACE .XXX: ± .010 [0.254] | | MTE AN MBL POWER ELECTRONICS COMPANY N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455.4683 262.253.8200 | | SNAP CHANNEL REACTOR | | |
| | | DRAWN JP | DATE 07/30/12 | | | |
| | | CHECKED JH | DATE 08/07/12 | | | |
| | | APPROVED JH | DATE 08/07/12 | SIZE D | DWG No. CD RLW-07P501 | REV 04 |
| | | SCALE 2:1 | | SHEET 1 OF 1 | | |