APPROX. WEIGHT (LBS)
72

ECO No	DESCRIPTION	REV BY	DATE
M12156	ADDED SHUNT LABEL	KV	12/09/19



TOP VIEW



BOTTOM VIEW





DETAIL B (6 PLACES)



DETAIL A (2 PLACES)



DETAIL C (3 PLACES)



FRONT VIEW



SIDE VIEW





CUSTOMER CONNECTION DETAIL VIEW

NOTES:

1. TERMINAL WIRE RANGE: 4-14 AWG.
2. TERMINAL SCREW TIGHTENING TORQUE: 16 IN\LBS.
3. REFER TO USER MANUAL FOR COMPLETE INSTALLATION INSTRUCTIONS.
4. FILTER INCLUDES: CAP-537SW (QTY. 2)

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE POWER QUALITY. SOLVED.

N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

DRAWN	DATE
MN	01/23/19
CHECKED	DATE
KV	12/09/19
APPROVED	DATE
PY	12/09/19

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

SWG 135A 208-240V 2-8kHz
FILTER, OPEN PANEL

SIZE	DWG No.	REV
D	CD SWGM0135A	01
SCALE 1:2		SHEET 1 OF 1