


APPROX. WEIGHT LBS
21

ECO No	DESCRIPTION	REV BY	DATE
M9807	REPLACED BRACKET -109 W/162	JT	03/22/16

NOTE

1. TIGHTEN STANDOFF SCREWS TO 58 IN/LBS. TORQUE, MAX

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION					
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION CAPPANEL 78 uF/PHASE					
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE: ANGLES: ± 1 ° 1 PLACE .X: ± .1 [2.5] 2 PLACE .XX: ± .01 [0.25] 3 PLACE .XXX: ± .005 [0.127]	 POWER QUALITY. SOLVED. N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455-4683 262.253.8200	DRAWN	JT					DATE	01/22/15
		CHECKED	RH	DATE	04/04/16				
		APPROVED	RH	DATE	04/04/16		SCALE	1:4	SHEET 1 OF 1