

APPROX. WEIGHT (LBS)
1536


ECO No	DESCRIPTION	REV BY	DATE

D


C

B

A



FRONT VIEW  
(PANELS REMOVED)




BOTTOM VIEW

LUG VIEW  
(6 PLACES)


( $\varnothing$ .56 X 1.00[24.40]  
[14.29]  
SLOT, 8 PLACES)

A


B




TOP VIEW  
(PANELS REMOVED)





SIDE VIEW



DETAIL B  
CUSTOMER CONNECTION  
DETAIL VIEW (THERMAL)



DETAIL A  
CUSTOMER CONNECTION  
DETAIL VIEW (GROUND)



CUSTOMER CONNECTION  
DETAIL VIEW

**NOTES:**

1. TIGHTEN TERMINAL BLOCK SCREWS TO 16 IN/LBS. TORQUE.
2. TERMINAL WIRE RANGE: 4 - 14 AWG
3. TERMINAL WIRE RANGE: 6 AWG - 250 MCM
4. TIGHTEN TERMINAL BLOCK SCREWS TO 275 IN/LBS. TORQUE.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION		
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:  ANGLES: ± 1 °  1 PLACE .X: ± .1 [2.5]  2 PLACE .XX: ± .03 [0.76]  3 PLACE .XXX: ± .010 [0.254]	POWER QUALITY. SOLVED.  N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455-4683 262.253.8200	DRAWN	DATE	SWG 1000A 600V 2-8kHz FILTER, NEMA 3R ENCL.		
		WF	10/01/18			
		CHECKED	DATE			
		WF	10/01/18			
		APPROVED	DATE	SIZE	DWG No.	REV
		TL	10/09/18	D	CD SWGW1000E	00
				SCALE	1:8	SHEET 1 OF 1